

Technical Data Sheet Aseptic Valve DN50

General Information:

Part Number: 843190 **Part Description:** Aseptic Valve DN50 – Click
Part Number: 843197 **Part Description:** Aseptic Valve DN50 – Tread
Application: Used for aseptic filling
Industries: Dairy and fruit ingredients
Connection: DN50 DIN11851 RD78x1/6
Steam temp: Max. 125°C
Irradiation: Max. 40kGy

Application areas:

- Combo Life
- Excelsior Hybrid
- Horem
- Buckhorn
- Cardbox -solutions

Product overview



Parts, Material, Colour

Valve Housing	: PK, light grey	O-rings	: NBR, black
Valve House Inlet	: PK, light grey	Screw cap	: PP, orange, blue, white
Gasket	: Silicone,	Handle	: PP, orange, blue
Disc flap	: PK, light grey	Axle	: Zinc, galvanised
D-ring	: NBR, blue		

Configurations

Screw Cap's

Blue, orange, white



Handle's

fix (orange), pluggable (blue)



IBA micro seal

yellow



Connection

2" Fenco Spout – PE, Nature , Internal Tread Yes/No



Protection foam

PE, white



Arca adapter

PP, Natur



**The information listed above is supplied in good faith and does not compromise a specification or warranty of any kind, either expressed or implied, including those of merchantability and fitness purpose. Customers should determine the sustainability of these materials for their specific use based upon their own internal criteria. Tests on individual samples may vary from those shown.*

Technical Data Sheet Aseptic Valve DN50

Dimensions

Packaging dimensions

Weight : 200g
Pieces per Box : 90

Aseptic Valve DN50 product configurations

Our Aseptic Valve is available in many different varieties. You can configure it to meet the needs of your specific filling/discharging system.

C	-	BC	-	BH	-	FS	-	AA	-	WP
---	---	----	---	----	---	----	---	----	---	----

Connection Type

C = Click
 T = Thread

Screw Cap

BC = Blue Cap
 OC = Orange Cap
 WC = White Cap

Handle

BH = Blue Handle
 OH = Orange Handle

Connection

FS = 2" Fenco Spout
 TS = 2" Thread Spout

Adaptor

AA = Arca Adapter
 NA = No Adapter

Protection Foam

WP = With Protection
 NP = No Protection